



# GS710

## Shock sensor

### Shock Sensor

---

The GS710 shock sensor offers a versatile solution for detection of forced entry through windows and doors. It can be mounted throughout a 360 degrees axis, vertically and horizontally, by ensuring that the brand logo is readable from left to right. The GS710 has been developed to offer an aesthetically superior low profile design with extra features to ease installation.

The GS711 has a built-in magnetic contact for double protection on opening doors and windows.

### Superior Detection

---

Its unique design enables the shock sensor to discriminate between a real break-in attempt and everyday background noise by measuring the shock frequency caused by the displacement in the protected structure.

The sensor is designed to activate (contact will open) when an acceleration greater than 1G is detected. This could be caused, for example by a strong blow or high speed drill because the frequencies of these shocks fall within the sensors range of detection.

### Adjustable Sensitivity

---

The shock sensors can be connected directly to control panels which have zones with incorporated analysing facilities or can be used in conjunction with dedicated analyser boards (GS614 and GS615). In both cases, the analysing capability has two separate detection criteria: gross attack and pulse count. The gross attack threshold is designed to react to a single shock, while pulse count alarms when a pre-selected number of smaller shocks, occurring within a 30 second timing interval is reached.



### Details

---

- Reliable 24 hour loop perimeter protection
- Superior technology provides excellent detection and false alarm immunity
- Dual-position terminal block
- Suitable for all types of solid structures
- Versatile mounting through 360° axis
- Two spare terminals
- High quality electrical tamper
- Available analysers: GS614 & GS615

# GS710

## Shock sensor

### Technical specifications

---

#### General

---

Product type	Shock
--------------	-------

---

#### Detection

---

Range	Up to 6 m
-------	-----------

---

#### Wired/wireless

---

Wired-wireless	Wired
----------------	-------

---

#### Physical

---

Physical dimensions	27 x 25 x 72 mm (W x H x D)
---------------------	-----------------------------

---

---

Colour	White
--------	-------

---

#### Environmental

---

Operating temperature	-40 to +50°C
-----------------------	--------------

---

#### Mounting location

---

	Glass, window/door frame, wall or roof
--	--

---

#### LED

---

	No
--	----

---

