

Roller Shutter Contact

Code: RS007/G3/AB

RS007 Type AB | Roller Shutter Contact | Grade 3 | Aluminium | Multi Resistor



This roller shutter contact can be used in most security systems up to and including grade 1 & 2 as specified in EN50131-1:2006 and is compliant with EN50131-2-6:2008 and environmental class III. It operates as a normally closed circuit going open when the magnet housing is moved away from the contact housing. This contact can be used on roller shutter doors to detect the unauthorised entry of an intruder. The contact is sealed to prevent access to the inside.

Features & Benefits

- High Quality Alloy Finish
- Selectable (A,B)
- Other resistor value available
- Locating mechanism to aid alignment
- 45cm or 1 mtr Armoured cable lengths
- EN50131-2-6 Grade 3
- Environmental Class III



Security

EN50131-2-6 Grade	3
Tamper Protection	Internal & MID

Environmental

EN50130-5 class	Class III
IP Rating	42
Temperature range	-15°C - +40°C

Housing

Colour	Aluminium
Material	Aluminium
Contact Dimensions (mm)	83 x 86 x 32
Magnet Dimensions (mm)	83 x 86 x 32

Electrical

Maximum switching voltage (Vdc)	12Vdc
Maximum switching current (mA)	250
Connection type	Wired
No. of terminals	8 Wire
Contact type	Normally Closed
Contact Material	Rhodium & Ruthenium
Wire length (mm)	450

Features

Mode of operation	DP, EOL/FSL
Resistor Type	A, B
Operation Axes (X, Y, Z)	Y, Z
Pull-in gap (X, Y, Z)mm	23, 28
Suitable for Double Door	Yes
Suitable for Double Pole Sys	Yes
Connection type	Wired
No. of terminals	8 Wire

Mechanical

Colour	Aluminium
--------	-----------